




# NTN Bearing Driveshaft do Brasil



skf SAW 23540 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23540 TLC

SAW 23540 TLC Bearing 2D drawings and 3D CAD models

$d_a$	182.563 mm
$D_a$	359.999 mm
$C_a$	137.82 mm
$A_1$	203.2 mm
$A_2$	285.75 mm
S	4.763 mm
$b_a$	98.425 mm
H	422.275 mm
$H_1$	209.55 mm
$H_2$	85.725 mm
J min.	571.5 mm
J max.	635 mm
$J_1$	127 mm
L	749.3 mm
$N_1$	34.925 mm
$R_1$	122.237 mm
$R_2$	46.038 mm
$R_G$	1 NPT
$P_G$	1/4 NPT
h	63.5 mm
Housing	SAW 540
Bearing	23240 CCK/W33
Adapter sleeve assembly	SNW 140x7.3/16
Stabilizing ring	SR-40-34
Labyrinth ring	2 x LOR 159



## NTN Bearing Driveshaft do Brasil

PosiTrac Plus contact element	2 x B10724-159
End plug (suffix Y)	EPR 21
Max. speed for PosiTrac Plus seal	800 r/min
P <sub>60°</sub>	364 kN
P <sub>90°</sub>	218 kN
P <sub>120°</sub>	136 kN
P <sub>150°</sub>	120 kN
P <sub>180°</sub>	145 kN
P <sub>a</sub>	77 kN
Mass pillow block	210 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g