




NTN Bearing Driveshaft do Brasil



skf SAF 23048 KAT x 8.15/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 23048 KAT x 8.15/16

SAF 23048 KAT x 8.15/16 Bearing 2D drawings and 3D CAD models

d_a	227.012 mm
D_a	359.999 mm
C_a	107.798 mm
A_1	203.2 mm
A_2	390.525 mm
b_a	89.694 mm
H	422.275 mm
H_1	209.55 mm
H_2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J_1	127 mm
L	749.3 mm
N_1	34.925 mm
R_1	122.237 mm
R_2	42.862 mm
R_G	1 NPT
P_G	1/4 NPT
h	56.356 mm
Housing	SAF 048 KA
Bearing	23048 CCK/W33
Adapter sleeve assembly	SNP 3048x8.15/16
Stabilizing ring	2 x A8897
Taconite seal	TER 552
End plug (suffix Y)	X-5217-4



NTN Bearing Driveshaft do Brasil

Max. speed for Taconite seal	340 r/min
P _{60°}	364 kN
P _{90°}	218 kN
P _{120°}	136 kN
P _{150°}	120 kN
P _{180°}	145 kN
P _a	66.7 kN
Mass pillow block	181 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N · m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g