




NTN Bearing Driveshaft do Brasil



skf SSAFS 22522 x 4 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22522 x 4 TLC

SSAFS 22522 x 4 TLC Bearing 2D drawings and 3D CAD models

d_a	101.6 mm
D_a	200 mm
C_a	62.89 mm
A_1	120.65 mm
A_2	165.1 mm
S	4.763 mm
b_a	50.006 mm
H	244.475 mm
H_1	125.425 mm
H_2	52.388 mm
L	419.1 mm
R_1	67.866 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	45.244 mm
Housing	SSAFS 522
Bearing	22222 EK
Adapter sleeve assembly	SNW 22x4
Stabilizing ring	SR-22-19
Labyrinth ring	2 x LOR 110
PosiTrac Plus contact element	2 x B10724-109
End plug (suffix Y)	EPR 13
Max. speed for PosiTrac Plus seal	1450 r/min



NTN Bearing Driveshaft do Brasil

P_{60°	178 kN
P_{90°	107 kN
P_{120°	66.7 kN
P_{150°	59.6 kN
P_{180°	72.5 kN
P_a	17.3 kN
Mass pillow block	54 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	232.47 g