



NTN Bearing Driveshaft do Brasil



44,45 mm x 83,058 mm x 25,4 mm NTN
4T-25580/25522 Single row tapered roller bearings

Bearing No. 4T-25580/25522

Size	44.45x83.058x25.4 mm
Bore Diameter	44,45 mm
Outer Diameter	83,058 mm
Width	25,4 mm
d	44,45 mm
D	83,058 mm
T	25,4 mm
B	25,4 mm
C	19,114 mm
a	17.7 mm
rs min	3.5 mm
r1s min	2 mm
e	0.33
Y2	1.79
Y0	0.99
Mass	0.55 kg
Dynamic load, C	76 kN
Rating life coefficient, A2	1.4
Static load, C0	98 kN
Nlim (oil)	6,000 rpm
Nlim (grease)	4,500 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.43 Hz

4T-25580/25522 Bearing 2D drawings and 3D CAD models



NTN Bearing Driveshaft do Brasil

frequency, FTF	
Characteristic rolling element frequency, BSF	7.06 Hz
Characteristic outer ring frequency, BPF0	8.21 Hz
Characteristic inner ring frequency, BPF1	10.79 Hz
ra max	3.5 mm
r1a max	2 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.574
Product Group	B04334