



NTN Bearing Driveshaft do Brasil



skf SALKAC 10 M Spherical plain bearings and rod ends with a male thread

Bearing No. SALKAC 10 M

SALKAC 10 M Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.05
EAN	7316577069054
Product Group	B04286
Stud Profile	Male
Mounting Thread	M10 X 1.5
Thread Direction	Left Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Bronze
Relubricatable	Yes
Enclosure	Open
Other Features	3 Piece Zinc Plated Outer
Long Description	10MM Bore; 10.5MM House Width; Male Stud Profile; M10 X 1.5; Left Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Bron
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod Ends



NTN Bearing Driveshaft do Brasil

UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SALKAC 10 M
Weight / LBS	0.119
d	0.394 Inch 10 Millimeter
Housing Width	0.413 Inch 10.5 Millimeter
Ball Width	0.551 Inch 14 Millimeter
bore diameter:	10 mm
ball material:	Steel
misalignment angle:	13 °
race material:	Bronze
shank thread length:	28 mm
radial static load capacity:	10.8 kN
rod end type:	Male Threaded
operating temperature range:	-30 to +180 ° F
shank thread size:	M10
head diameter:	29 mm
thread direction:	Left Hand
head width:	10.5 mm
grade:	Commercial/Industrial
ball width:	14 mm
lubrication type:	With Lubrication Fitting
length to ball center:	48 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, DIN 3405:1986
d	10 mm
d ₂ max.	29 mm



NTN Bearing Driveshaft do Brasil

B	14 mm
G	M 10
C ₁ max.	11.5 mm
h	48 mm
	13 °
d _k	19 mm
l ₁ min.	28 mm
l ₂ max.	64 mm
r ₁ min.	0.3 mm
Basic dynamic load rating C	10 kN
Basic static load rating C ₀	10.8 kN
Specific dynamic load factor K	50 N/mm ²
Material constant K _M	330
Mass rod end	0.054 kg